Change Trigger Module Direction

Press!

1. To remove the KDC180 from the trigger module, press and hold each tab on both sides of the trigger module cap while pulling the KDC180 upward. (A)

2. Rotate trigger module 180 degrees and insert the KDC180 in to the trigger module cap until both sides click. (B)

Click!

2-Slot and 10-Slot Charging Cradles KDC180 Models KDC180U Wearable 0.5W UHF Reader KDC180H 2D Imager KDC180H 2D Imager with Keypad KDC180H 2D Imager with Inductive Charging KDC180H 2D Imager with 0.5W UHF Reader

ΚΟΛΜΤΛΟ

Micro USB Cable

KBLED41 BLE Donale


Protective Rubber Boot

Additional Accessories

Finger Trigger Glove

116 Village Blvd, Ste 305, Princeton, NJ 08540 +1 609-256-4700 p +1 609-228-4373 f info@koamtac.com | www.koamtac.com

KOVWLVC KDC180 Double Ring Scanner & Ring Scanner Manual




*KDC180 Inductive / Keypad / 0.5W UHF Models are assembled the same way.

*Only for Double Ring Scanner.


Replacing the Ring Band

3. While pressing the "PUSH" button, slide the ring band in the opposite direction of the trigger button as shown. (C)



*The replacement ringband description applies to both double ring scanners and ring scanners.

3. Align the sides of the ring band with the rails on the trigger module (D). Insert the ring band by pushing the ring band into the trigger module rail until it clicks. (E)




5. Spread both sides of hook and loop band as shown and detach from the ring band. Remove the band from the finger pad. (F)

F

*To reattach the ring band, perform the previous steps in reverse.

Band Storage

6. Put your fingers through the band and set it to a comfortable length. If the band is too long, move the finger pad on both sides to store the band as shown. (G)



*If the original band is too large, use the enclosed short band.